

Safety Data Sheet

MasterSeal TC 275 PART A also CONIPUR 275 TOP COAT PTA

Revision date : 2011/11/29
Version: 1.0

Page: 1/7
(30367672/SDS_GEN_US/EN)

1. Product and Company Identification

Company
BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

24 Hour Emergency Response Information
CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

2. Hazards Identification

Emergency overview

WARNING:
CONTAINS MATERIAL WHICH CAN CAUSE CANCER.
MAY CAUSE EYE IRRITATION.
MAY CAUSE SKIN IRRITATION.
Ingestion may cause irritation to mucous membranes.
Avoid contact with the skin, eyes and clothing.
Wash thoroughly after handling.
Keep container tightly closed.
No exposure to respirable Crystalline (quartz) Silica anticipated with recommended use of product.

State of matter: liquid
Colour: various
Odour: faint odour

Potential health effects

Primary routes of exposure:

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity:

No data available.

Irritation / corrosion:

May cause slight irritation to the eyes. May cause slight irritation to the skin. The product has not been tested. The statement has been derived from products of a similar structure or composition.

Chronic toxicity:

Reproductive toxicity: The chemical structure does not suggest such an effect. The product has not been tested. The statement has been derived from the properties of the individual components.

Safety Data Sheet

MasterSeal TC 275 PART A also CONIPUR 275 TOP COAT PTA

Revision date : 2011/11/29
Version: 1.0

Page: 2/7
(30367672/SDS_GEN_US/EN)

Teratogenicity: The chemical structure does not suggest such an effect. The product has not been tested. The statement has been derived from the properties of the individual components.

Genotoxicity: The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from the properties of the individual components.

Potential environmental effects

Aquatic toxicity:

At the present state of knowledge, no negative ecological effects are expected. There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statement has been derived from products of a similar structure or composition.

Bioaccumulation / bioconcentration:

Discharge into the environment must be avoided.

3. Composition / Information on Ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
14808-60-7	>= 15.0 - <= 40.0 %	crystalline silica
7727-43-7	>= 10.0 - <= 30.0 %	Barium sulfate
13463-67-7	>= 3.0 - <= 7.0 %	Titanium dioxide
770-35-4	>= 1.0 - <= 5.0 %	1-phenoxypropan-2-ol
108-65-6	>= 0.5 - <= 1.5 %	1-methoxy-2-propylacetate

4. First-Aid Measures

General advice:

First aid personnel should pay attention to their own safety. Remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Rinse mouth immediately with water. Seek medical attention if necessary. Do not induce vomiting unless told to by a poison control center or doctor.

5. Fire-Fighting Measures

Flash point:	93.34 °C	(ASTM D56, closed cup)
	200.01 °F	(ASTM D56, closed cup)
Lower explosion limit:	0.7 %(V)	
Upper explosion limit:	9.4 %(V)	

Suitable extinguishing media:

foam, water spray, dry powder, carbon dioxide

Safety Data Sheet

MasterSeal TC 275 PART A also CONIPUR 275 TOP COAT PTA

Revision date : 2011/11/29
Version: 1.0

Page: 3/7
(30367672/SDS_GEN_US/EN)

Unsuitable extinguishing media for safety reasons:
water jet

Hazards during fire-fighting:
carbon monoxide, carbon dioxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Protective equipment for fire-fighting:
Wear a self-contained breathing apparatus.

Further information:
The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions:
Use personal protective clothing. Do not breathe vapour/aerosol/spray mists. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions:
Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Cleanup:
For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.
For large amounts: Pump off product.

7. Handling and Storage

Handling

General advice:
Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

Protection against fire and explosion:
The product does not contribute to the spreading of flames, nor is it self combustible, not explosive.

Storage

General advice:
Keep container tightly closed.

8. Exposure Controls and Personal Protection

Components with workplace control parameters

Safety Data Sheet

MasterSeal TC 275 PART A also CONIPUR 275 TOP COAT PTA

Revision date : 2011/11/29
Version: 1.0

Page: 4/7
(30367672/SDS_GEN_US/EN)

crystalline silica	OSHA	TWA value 2.4 millions of particles per cubic foot of air Respirable ; The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation. TWA value 0.1 mg/m3 Respirable ; The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation. TWA value 0.3 mg/m3 Total dust ; The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation.
Barium sulfate	ACGIH OSHA	TWA value 0.025 mg/m3 Respirable fraction ; PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ;
Titanium dioxide	ACGIH OSHA ACGIH	TWA value 10 mg/m3 ; PEL 15 mg/m3 Total dust ; TWA value 10 mg/m3 ;

Personal protective equipment

Respiratory protection:

When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

Hand protection:

Wear chemical resistant protective gloves.

Eye protection:

Safety glasses with side-shields.

Body protection:

depending upon conditions of use., Cover as much of the exposed skin as possible to prevent all skin contact., light protective clothing

General safety and hygiene measures:

Avoid contact with the skin, eyes and clothing. In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form:	liquid	
Odour:	faint odour	
Colour:	various	
Boiling point:	140.00 - 242.78 °C	
Density:	approx. 1.63 g/cm3 13.35 - 13.85 lb/USg	(20 °C) (73 °F)
Vapour density:		Heavier than air.
Solubility in water:		(15 °C) not soluble

10. Stability and Reactivity

Conditions to avoid:

Safety Data Sheet

MasterSeal TC 275 PART A also CONIPUR 275 TOP COAT PTA

Revision date : 2011/11/29
Version: 1.0

Page: 5/7
(30367672/SDS_GEN_US/EN)

Avoid extreme temperatures.

Substances to avoid:

strong acids, strong bases, strong oxidizing agents

Hazardous reactions:

The product is stable if stored and handled as prescribed/indicated.

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

Oxidizing properties:

Oxidizing.

11. Toxicological information

Acute toxicity

Information on: 1-methoxy-2-propylacetate

Assessment of acute toxicity:

Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact.

Irritation / corrosion

Information on: 1-phenoxypropan-2-ol

Assessment of irritating effects:

Not irritating to the skin. May cause severe damage to the eyes.

Carcinogenicity

Information on: crystalline silica

The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen.

NTP listed carcinogen

Information on: Titanium dioxide

IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.

Other Information:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from products of a similar structure and composition.

12. Ecological Information

Degradability / Persistence

Biological / Abiological Degradation

Safety Data Sheet

MasterSeal TC 275 PART A also CONIPUR 275 TOP COAT PTA

Revision date : 2011/11/29
Version: 1.0

Page: 6/7
(30367672/SDS_GEN_US/EN)

Evaluation: Inherently biodegradable.
The insoluble fraction can be removed by mechanical means in suitable waste water treatment plants.

Other adverse effects:

Ecological data are not available. Do not allow to enter soil, waterways or waste water channels.

13. Disposal considerations

Waste disposal of substance:

Recommendations: Use excess product in an alternate beneficial application. Do not discharge into drains/surface waters/groundwater. Dispose of in accordance with local authority regulations.

Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

OSHA hazard category:

IARC 1, 2A or 2B carcinogen; NTP listed carcinogen; Chronic target organ effects reported; OSHA PEL established; ACGIH TLV established; Oxidizer

EPCRA 311/312 (Hazard categories):

Acute; Chronic

CERCLA RQ

1000 LBS

CAS Number

108-88-3; 7727-43-7

Chemical name

Toluene; Barium sulfate

Safety Data Sheet

MasterSeal TC 275 PART A also CONIPUR 275 TOP COAT PTA

Revision date : 2011/11/29
Version: 1.0

Page: 7/7
(30367672/SDS_GEN_US/EN)

10 LBS 71-43-2; 106-99-0 Benzene; butadiene

State regulations

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
MA, NJ, PA	14808-60-7	crystalline silica
MA, NJ, PA	7727-43-7	Barium sulfate
MA, NJ, PA	13463-67-7	Titanium dioxide

CA Prop. 65:

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

16. Other Information

HMIS III rating

Health: 2⁺ Flammability: 1 Physical hazard: 0

NFPA and HMIS use a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates extreme danger. Although similar, the two rating systems are intended for different purposes, and use different criteria. The NFPA system was developed to provide an on-the-spot alert to the hazards of a material, and their severity, to emergency responders. The HMIS system was designed to communicate workplace hazard information to employees who handle hazardous chemicals.

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

MSDS Prepared by:

BASF NA Product Regulations
msds@basf.com
MSDS Prepared on: 2011/11/29

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET