Safety Data Sheet

I. Product and Company Identification

PRODUCT: ISOFLEX 900 SAND

MANUFACTURER: LymTal International, Inc.

4150 S. Lapeer Rd. Orion, MI 48359

www.lymtal.com

For Non-Emergency Questions,

Hours 8AM To 4PM Eastern Standard Time

(248) 373-8100

EMERGENCY CONTACT: 24-Hour Chemtrec (800)424-9300

Chemtrec, D.C. Area (800)483-7616

II. Hazards Identification

Classification of the Substance or Mixture:



Carcinogenicity, CAT 1A; STOT Repeated Exposure, CAT 1(Lungs, Respiratory System)



STOT Single Exposure, CAT 3A (Lungs, Resp Irritation)

Signal Word: DANGER

Hazard Statements:

H335 May Cause Respiratory Irritation Stot Single Exposure, Cat 3A, (Lungs, Respiratory System)

H350 May Cause Cancer (Inhalation) Carcinogenicity, CAT 1A

H372 Causes Damage To Organs Through

Prolonged Or Repeated Exposure Stot Repeated Exposure, Cat 1 (Lungs, Respiratory System)

Precautionary Statements:

P102 Keep Out Of Reach Of Children

P103 Read Label Before Use

P201 Obtain Special Instructions Before Use

P202 Do Not Handle Until All Safety Precautions Have Been Read And Understood

P260 Do Not Breathe Dust/Fume/Gas/Mist/Vapors/Spray

P264 Wash Thoroughly After Handling

P270 Do Not Eat/Drink/Smoke While Using This Product P271 Use Only Outdoors Or In A Well Ventilated Area

P280 Wear Protective Gloves/Protective Clothing/Eye Protection/Face Protection

P285 In Case Of Inadequate Ventilation Wear Respiratory Protection

P308+P313 If Exposed Or Concerned: Get Medical Advice/Attention

P309+P311 If Exposed Or If You Feel Unwell: Call A Poison Center Or Doctor

P304+P340+P314 If Inhaled: Remove Person To Fresh Air And Keep Comfortable For Breathing, Get Medical

Advice/Attention If You Feel Unwell.

LymTal International, Inc. ISOFLEX 900 SAND Page 1 of 5

P403+P233 Store In A Well Ventilated Place. Keep Container Tightly Closed

P405 Store Locked Up

P501 Dispose Of Contents/Container In Accordance With Local/Regional/National/International/

Regulations

III. Composition/Information on Ingredients

Ingredients:CAS #:CONTENTCrystalline Silica (Quartz)14808-60-7100%

California Proposition 65 ingredients

None

Section 313 Supplier Notification

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 (40CFR372)

None

IV. First Aid Measures

<u>Inhalation</u> Remove victim from exposure. If difficulty with breathing, administer oxygen and

seek medical assistance

WARNING! HARMFUL IF INHALED. OVEREXPOSURE MAY CAUSE LUNG DAMAGE. MAY CAUSE EYE IRRITATION. INHALATION CANCER HAZARD. CONTAINS QUARTZ WHICH CAN CAUSE CANCER. Risk of cancer depends

upon duration and level of exposure.

Eyes Flush eyes with cold water for a minimum of 15 minutes, lifting lower and upper eye

lids throughout. Seek immediate medical attention.

Skin Immediately remove contaminated clothing. Wash thoroughly with soap and water. If

irritation persists seek medical attention. Wash contaminated clothing before reuse.

<u>Ingestion</u> Do not induce vomiting, get immediate medical attention, if vomiting occurs

spontaneously keep head below hips to prevent aspiration of liquids into lungs. Do

not give anything by mouth to an unconscious person

V. Fire Fighting Methods

HMIS Hazard Rating No. 0

<u>Flash Point:</u> Not flammable

<u>General Hazard:</u> Not Applicable.

Auto-Ignition Temp.: Not Applicable.

Limits of Flammability LEL: Not Available UEL: Not Available

Extinguishing Media Not Applicable.

Special Fire & Unusual Hazards None

LymTal International, Inc. ISOFLEX 900 SAND Page 2 of 5

VI. Accidental Release Measures

Action To Take For Spills/ Leaks: Ventilate area, wear appropriate protective gear, contain spill, salvage, clean up residue by sweeping and collect in suitable containers and follow waste disposal method below. Waste Disposal Method: Handle disposal of waste material in a manner that complies with local, state, province and federal regulation. Landfill if solidified, or incineration at agency approved waste-disposal facilities.

VII. Handling And Storage

Store Dry At 50-95°F. Condition Material To 65-85°F Before Using

VIII. Exposure Controls / Personal Protection

<u>Ventilation</u>: Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to avoid build up of dust.

<u>Personal Protection Equipment:</u> Do NOT wear contact lenses when working with this material. Use chemical goggles/safety glasses with side shields and impervious gloves. Wear clothing with long sleeves and pants. In operations where dust / mists can be generated or the exposure limits for crystalline silica exceeded, wear a NIOSH/MSHA approved dust / fume respirator selected by a technically qualified person for the specific work conditions. Wear respirator protection whenever airborne concentrations exceed TLV ceilings or TWA, use NIOSH approved respirators for listed hazard.

Confined spaces, room, or tanks are areas where concern for TLV's is especially important. Reference OSHA regulation CFR 29 1910.134 for recommended respiratory protection.

IX. Physical And Chemical Properties

Water/Oil Distribution Boiling Point (°C): N/A N/A Coefficient: Solubility in Water: N/A VOC Content g/l: 0 g / L Freezing Point (°C): Specific Gravity @20° C N/A 2.7 Vapor Pressure @ 20° C N/A N/A :Ha Evaporation Rate: Vapor Density N/A N/A Odor Threshold: N/A Odor: Aggregate Appearance: Solid aggregate N/A = Not Available N/D=NOT Determined Ca. = Approximate

X. Stability And Reactivity

HMIS Hazard Rating No. 0

<u>Stability</u> Stable

<u>Incompatibility:</u>
Avoid hydrofluoric acid as this will react with the silica to generate

the corrosive gas SiF4.

Hazardous Decomposition Products Not Applicable

Conditions To Avoid Hydrofluoric acid

LymTal International, Inc. ISOFLEX 900 SAND Page 3 of 5

XI. Toxicity Information

HMIS Hazard Rating No. 1

PRIMARY ROUTE OF ENTRY: Inhalation, dermal, skin and eyes.

Effects Of Overexposure

<u>Inhalation:</u> May cause silicosis of the lungs over time without dust masks etc.

WARNING! HARMFUL IF INHALED. OVEREXPOSURE MAY CAUSE LUNG DAMAGE. MAY CAUSE EYE IRRITATION. INHALATION CANCER HAZARD. CONTAINS QUARTZ WHICH CAN CAUSE CANCER. Risk of

cancer depends upon duration and level of exposure.

<u>Eyes:</u> Contact can cause severe irritation, redness, tearing and blurred vision.

Skin Contact: May cause moderate skin irritation.

Ingestion: May cause permanent damage to the mouth throat and stomach.

XII. Ecological Information

Marine Pollutant: NL

(NL = Not Listed; P = Moderate; PP = Severe; ND = Not Determined)

XIII. Disposal Considerations

Handle disposal of waste material in a manner that complies with all applicable local, state, provincial and federal regulations.

XIV. Transport Information

DOT SHIPPING INFORMATON

DOT Proper Shipping Name: NOT REGULATED

XV. Regulatory Information

OSHA Hazard Communication Standard See section II

(29 CFR 1910.1200)

CERCLA/ Super fund (40 CFR 117,302) N/A SARA Extremely Hazardous Substances N/A

(40 CFR 355)

SARA Hazard Categories (40 CFR 370) N/A SARA Toxic Chemicals (40 CFR 372) None

Inventory Status The chemicals in this product are listed on the US

TSCA Chemical Substance Inventory and the

Canadian Domestic Substances List.

LymTal International, Inc. ISOFLEX 900 SAND Page 4 of 5

XVI. Other Information
THE INFORMATION HEREIN HAS BEEN COMPLIED FROM SOURCES BELIEVED TO BE RELIABLE AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, LymTai INTERNATIONAL INC. CANNOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE ANY WARRANTIES, NOR ASSUMES ANY LIABILITY, FOR ITS USE.
Date of Preparation/ Last Revision: 5/21/2015

LymTal International, Inc. ISOFLEX 900 SAND Page 5 of 5